

EXPRESS MAIL CERTIFICATE

I HEREBY CERTIFY THAT THIS CORRESPONDENCE IS
BEING DEPOSITED WITH THE UNITED STATES
POSTAL SERVICE AS EXPRESS MAIL, POSTAGE
PREPAID, IN AN ENVELOPE ADDRESSED TO:
ASSISTANT COMMISSIONER FOR PATENTS,
WASHINGTON, D.C. 20231 ON

April 4, 2001

SAID ENVELOPE HAVING AN EXPRESS MAIL MAILING
LABEL NUMBER OF: EK565877855US

Margaret B. White

Margaret B. White

**POLYOLEFIN FOAM COMPOSITE STRUCTURE AND
METHOD FOR MAKING THE SAME**

This Application is a Continuation-in-Part of U.S. Serial No.
09/472,088, filed December 23, 1999.

BACKGROUND OF THE INVENTION

The present invention relates generally to polyolefin foams and,
more particularly, to extruded polyethylene foam sheets having a coating
disposed thereon for bonding the polyethylene foam sheet to a
polypropylene foam sheet.

Polyolefin foams, particularly polyethylene foams, and methods for
manufacturing such foams are well known in the art. See, e.g., U.S. Pat.
Nos. 5,348,984 (Lee), 5,462,974 (Lee), and 5,667,728 (Lee), the
disclosures of which are incorporated herein by reference thereto. One of
the most common polyethylenes used is low density polyethylene (LDPE).

While polyethylene (PE) possesses a number of beneficial physical
and chemical properties when used to produce a foamed sheet, a
disadvantage of PE is that extruded foam sheets made therefrom have a
flexural modulus that is lower than would otherwise be desired for

certain applications. For example, PE foams are commonly used to manufacture a type of flotation article known as a "bodyboard," which is a generally planar foamed structure of various shapes and sizes that allows individuals to be carried forward by oceanic waves as the waves break near the shore, i.e., to ride or "surf" the waves. This is commonly accomplished by grasping the edges of the bodyboard with a portion of the upper body positioned above, and often in contact with, the upper surface of the board. Individuals engaging in such activity generally prefer that the bodyboard be as stiff as possible as this allows the individual to maneuver the board to control somewhat the individual's direction of travel relative to the wave surface upon which the individual is "surfing." Too much flexure in the waveboard detracts from this ability to maneuver the board along the wave surface. Accordingly, efforts have been made to increase the stiffness of the foam used to make bodyboards.

One possible solution would be to construct the bodyboard from polypropylene (PP) foam, which is much stiffer than PE foam. However, PP foam has generally been found to be overly stiff and brittle, resulting in a bodyboard that is too easily damaged (e.g., gouged) and difficult to firmly grasp and handle, particularly when wet. In addition, PP foam has a surface texture that is uncomfortable against the skin, especially when rubbed against the skin as generally occurs during bodyboarding.

Another possibility would be to form a composite structure that includes a PE foam sheet bonded to a PP foam sheet. The PE foam sheet would provide comfort, grippability, and durability, while the PP foam sheet would provide increased stiffness and performance. Unfortunately, PP and PE foams are not chemically compatible and will not readily adhere to one another. Delamination is therefore a significant problem for PE foam/PP foam laminates.

It may be possible, in certain cases, to use special chemical adhesives (i.e., glues) to bond PP and PE foams. However, such adhesives are expensive. In addition, the process of coating and bonding is tedious and costly. The process involves slow production steps and
 5 the adhesives contain volatile organic solvents that are undesirable for release into the air. Extra equipment, therefore, is generally needed to recover the solvents, thus further adding to the expense and complexity of the adhesive coating process.

Accordingly, a need exists in the art for an economical and
 10 practical means for bonding PP foam to PE foam with sufficient strength that the resultant composite structure is suitable for commercial use, such as for bodyboards or other watersport applications.

SUMMARY OF THE INVENTION

15 That need is met by the present invention, which provides a composite structure, comprising:

- a. a foam sheet comprising polyolefin; and
- b. a coating disposed on at least one surface of the polyolefin
 20 foam sheet, the coating comprising at least one member selected from ethylene/propylene rubber, homogeneous ethylene/alpha-olefin copolymer, ethylene/acrylic acid copolymer, ethylene/vinyl acetate copolymer, and blends of the foregoing.

Advantageously, the coating is capable of bonding the polyolefin foam sheet to a second foam sheet having a different chemical composition
 25 than the polyolefin foam sheet at a bond strength of at least about 4 lb_f/inch.

In a preferred alternative embodiment of the invention, a multilayer composite structure comprises:

- a. a first foam layer comprising polyethylene homopolymer or copolymer;
- b. a second foam layer comprising polypropylene homopolymer or copolymer; and
- 5 c. a coating disposed between and bonding the first and second foam layers together at a bond strength of at least about 4 lb_f/inch, the coating comprising at least one member selected from ethylene/propylene rubber, homogeneous ethylene/alpha-olefin copolymer, ethylene/acrylic acid copolymer, ethylene/vinyl acetate copolymer, and blends of the
- 10 foregoing.

In accordance with yet another embodiment of the invention, a method for making a composite structure is provided, comprising:

- a. providing a foam sheet comprising polyolefin; and
- b. coating at least one surface of the polyolefin foam sheet, the
- 15 coating comprising at least one member selected from ethylene/propylene rubber, homogeneous ethylene/alpha-olefin copolymer, ethylene/acrylic acid copolymer, ethylene/vinyl acetate copolymer, and blends of the foregoing,

whereby, the coating is capable of bonding the polyolefin foam sheet

20 to a second foam sheet having a different chemical composition than the polyolefin foam sheet at a bond strength of at least about 4 lb_f/inch.

As is explained in further detail below, the invention provides a means for bonding PE foam to PP foam with a solventless coating process, i.e., via a coating that contains substantially no volatile organic solvent.

25 Further, the resultant bond strength between the PE and PP foam sheets of at least 4 lb_f/inch is sufficiently high for commercial watersport applications.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an elevational, cross-sectional view of a composite structure in accordance with the present invention;

FIG. 2 is an elevational, cross-sectional view of an alternative composite structure in accordance with the present invention; and

FIG. 3 is a schematic view of a preferred process for making the composite structure shown in FIG. 1.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 illustrates a composite structure 10 in accordance with the present invention, including a foam sheet 12 and a coating 14 in adherence with the foam sheet and disposed on surface 16 thereof.

The foam sheet 12 in accordance with the invention comprises a polyolefin, such as polyethylene homopolymer or copolymer or polypropylene homopolymer or copolymer. Examples of useful polyethylene homopolymers include low density polyethylene and high density polyethylene. Polyethylene copolymers may include, e.g., homogeneous ethylene/alpha-olefin copolymers (i.e., metallocene/single-site catalyzed copolymers of ethylene and, e.g., one or more C₃ to C₁₀ alpha-olefin comonomers) or heterogeneous (i.e., Ziegler-Natta catalyzed) ethylene/alpha-olefin copolymers. A preferred polyethylene is low density polyethylene (LDPE) having a melt flow index ranging from about 1 to about 40 and a density ranging from about 0.915 to about 0.930 g/cc.

Various polypropylenes are suitable in accordance with the practice of the present invention, including atactic, isotactic, syndiotactic, long-chain branched, and propylene/ethylene copolymers. Preferred polypropylenes have a melt flow index ranging from about 1 to 20 and a density ranging from about 0.87 to 0.915 g/cc. Further, a high melt strength/long-chain branched polypropylene is preferred. Such

polypropylenes exhibit higher extensional viscosity when compared to other polypropylenes, resulting in beneficial strain hardening when the cells are expanded during the foaming process.

The foam sheet may have any desired thickness to suit the intended application, preferably ranging, e.g., from about 1/16 inch to about 5 inches. The foam may have any desired density, ranging, e.g., from about 1 to about 30 pounds/ft³. The density preferably ranges from about 1.5 to about 10 pounds/ft³ and, most preferably, from about 2 to about 8 pounds/ft³. The foam sheet preferably has at least about 70 % closed cells, more preferably about 80 % closed cells and, most preferably, at least about 90 % closed cells.

In a preferred embodiment, the polyolefin foam sheet 12 comprises polyethylene homopolymer or copolymer having a density ranging from about 0.4 to about 15 pounds/ft³, more preferably from about 1 to about 10 pounds/ft³, and most preferably from about 2 to about 8 pounds/ft³.

In an alternative preferred embodiment, the polyolefin foam sheet 12 comprises polypropylene homopolymer or copolymer having a density ranging from about 0.5 to about 30 pounds/ft³, more preferably from about 1 to about 10 pounds/ft³, and most preferably from about 1 to about 6 pounds/ft³.

Any conventional chemical or physical blowing agents may be used. Preferably, the blowing agent is a physical blowing agent such as carbon dioxide, ethane, propane, n-butane, isobutane, pentane, hexane, butadiene, acetone, methylene chloride, any of the chlorofluorocarbons, hydrochlorofluorocarbons, or hydrofluorocarbons, as well as mixtures of the foregoing.

The blowing agent may be mixed with the polyolefin in any desired amount to achieve a desired degree of expansion in the resultant foam. Generally, the blowing agent may be added to the polyolefin in an amount

ranging from about 0.5 to 80 parts by weight, based on 100 parts by weight of the polyolefin. More preferably, the blowing agent is present at an amount ranging from 1 to 30 and, most preferably, from 3 to 15 parts per 100 parts by weight of the polyolefin.

5 If desired or necessary, various additives may also be included with the polyolefin. For example, it may be desirable to include a nucleating agent (e.g., zinc oxide, zirconium oxide, silica, talc, etc.) and/or an aging modifier (e.g., a fatty acid ester, a fatty acid amide, a hydroxyl amide, etc.). Other additives that may be included if desired are pigments, colorants,
10 fillers, antioxidants, flame retardants, stabilizers, fragrances, odor masking agents, and the like.

 Foam in accordance with the present invention is preferably made by an extrusion process that is well known in the art. In such a process, the polyolefin is added to an extruder, preferably in the form of resin
15 pellets. Any conventional type of extruder may be used, e.g., single screw, double screw, and/or tandem extruders. In the extruder, the resin pellets are melted and mixed. A blowing agent is preferably added to the melted polyolefin via one or more injection ports in the extruder. Any additives that are used may be added to the melted polyolefin in the extruder
20 and/or may be added with the resin pellets. The extruder pushes the entire melt mixture (melted polyolefin, blowing agent, and any additives) through a die at the end of the extruder and into a region of reduced temperature and pressure (relative to the temperature and pressure within the extruder). Typically, the region of reduced temperature and pressure
25 is the ambient atmosphere. The sudden reduction in pressure causes the blowing agent to nucleate and expand into a plurality of cells that solidify upon cooling of the polymer mass (due to the reduction in temperature), thereby trapping the blowing agent within the cells.

Referring again to FIG. 1, coating 14 preferably has a thickness ranging from about 0.5 to about 20 mils (1 mil = 0.001 inch); more preferably from about 1 to about 8 mils; and most preferably between about 1 and 6 mils. Coating 14 comprises at least one member selected from ethylene/propylene rubber, homogeneous ethylene/alpha-olefin copolymer, ethylene/acrylic acid copolymer, ethylene/vinyl acetate copolymer, and blends of the foregoing.

Suitable ethylene/propylene rubbers include both ethylene/propylene copolymer rubber and ethylene/propylene/diene terpolymer rubber. Ethylene/propylene copolymer rubber may have an ethylene content of from about 30 to about 80 wt. % (with the balance comprising propylene) while ethylene/propylene/diene terpolymer rubber may have an ethylene content of about 30 to about 70 wt. % and a diene content of from about 1 to about 10 wt. % (again, with the balance comprising propylene). More preferably, the ethylene content ranges from about 50 to about 75 wt. %. The typically used diene monomers are generally selected from the easily polymerizable non-conjugated dienes and can be straight chain, hydrocarbon diolefins or cycloalkenyl-substituted alkenes, having about 6 to about 15 carbon atoms. For example, 1,4-hexadiene may be used to make ethylene/propylene/1,4 hexadiene terpolymer. Other examples of useful diene monomers are dicyclopentadiene and 2-methylene-5-norbornene compounds. The degree of unsaturation is usually in the range of 2 to 15 double bonds per 1000 carbon atoms, distributed randomly on the polymer chain. Typically, ethylene-propylene rubbers are made from monomers that have a specific gravity in the neighborhood of 0.87.

If desired, e.g., for reasons of economy, the ethylene/propylene rubber may be blended with another material, such as a polyethylene

homopolymer or copolymer, a polypropylene homopolymer or copolymer, or blends thereof.

Coating 14 may also comprise homogeneous ethylene/alpha-olefin copolymer. As is well understood in the art, a "homogeneous" ethylene/alpha-olefin copolymer refers to ethylene/alpha-olefin copolymerization reaction products of relatively narrow molecular weight distribution and relatively narrow composition distribution. Homogeneous ethylene/alpha-olefin copolymers are structurally different from heterogeneous ethylene/alpha-olefin copolymers, in that homogeneous ethylene/alpha-olefins exhibit a relatively even sequencing of comonomers within a chain, a mirroring of sequence distribution in all chains, and a similarity of length of all chains, i.e., a narrower molecular weight distribution. Furthermore, homogeneous ethylene/alpha-olefin copolymers are typically prepared using metallocene, or other single-site type catalysts, rather than using Ziegler Natta catalysts. Such single-site catalysts typically have only one type of catalytic site, which is believed to be the basis for the homogeneity of the polymers resulting from the polymerization. A homogeneous ethylene/alpha-olefin copolymer can, in general, be prepared by the copolymerization of ethylene and any one or more alpha-olefin. Preferably, the alpha-olefin is a C₃-C₂₀ alpha-monoolefin, more preferably, a C₄-C₁₂ alpha-monoolefin, still more preferably, a C₄-C₈ alpha-monoolefin. Still more preferably, the alpha-olefin comprises at least one member selected from the group consisting of 1-butene, 1-pentene, 1-hexene, and 1-octene.

Homogeneous, as opposed to heterogeneous, ethylene/alpha-olefin copolymers have been found to provide excellent adhesion between, e.g., a polyethylene foam sheet and a polypropylene foam sheet, and therefore are beneficially employed in a coating in accordance with the present invention. Preferred homogeneous ethylene/alpha-olefins have a density

of less than about 0.94 g/cc, more preferably less than 0.92 g/cc, and most preferably less than about 0.91 g/cc.

Ethylene/acrylic acid copolymer (EAA) has also been found to provide good adhesion between PE and PP foam sheets. Such materials are generally less preferred, however, due to their relatively high cost in comparison with EPR and homogeneous ethylene/alpha-olefin copolymer.

A highly preferred material for coating 14 is ethylene/vinyl acetate copolymer (EVA). Such material has been shown to provide excellent bonding with both PE and PP foam. Preferred EVAs have a vinyl acetate content of up to 33% by weight and a melt index of at least 3 g/10 min. If desired, the EVA may be blended with polyethylene homopolymer or with homogeneous or heterogeneous ethylene/alpha-olefin copolymer.

Advantageously, coating 14 may be substantially solventless, i.e., containing substantially no volatile organic carrier fluids to either evaporate into the environment or be recovered by expensive pollution-control equipment. This is because the coating in accordance with the invention is not a solvent-based adhesive but is, in a preferred embodiment, a thermoplastic polymer composition that can be melted and coated onto a surface of the foam sheet by, e.g., extrusion-coating or coextruding the coating onto the foam as described in more detail below. Instead of relying on evaporation of a solvent in order for the coating to cure, a thermoplastic coating in accordance with the present invention simply cools and solidifies, with little or no evaporation of volatile organic solvents.

At the same time, coating 14 has been found capable of bonding foam sheet 12 to a second foam sheet having a different chemical composition, i.e., different from that of foam sheet 12, at a bond strength of at least about 4 lb_f/inch. This has been determined to be the minimum acceptable bond strength for commercial applications, e.g., for bodyboard

or other watersport use. As demonstrated in the examples, EPR, homogeneous ethylene/alpha-olefin copolymer, EAA, and EVA have been shown to be capable of bonding PE foam to PP foam at a bond strength greater than 4 lb_f/inch. A more preferred bond strength is at least about 4.5 lb_f/inch.

When a second foam sheet, comprising a material of a different chemical composition than polyolefin foam sheet 12, is bonded via coating 14 to foam sheet 12, a number of combinations of different foam/foam laminates are possible. In one such combination, polyolefin foam sheet 12 having coating 14 thereon may comprise polyethylene homopolymer or copolymer while a second foam sheet bonded to surface 18 of coating 14 comprises polypropylene homopolymer or copolymer. The inverse is also possible, i.e., where the coated polyolefin foam sheet 12 comprises polypropylene homopolymer or copolymer and the second foam sheet bonded to surface 18 of coating 14 comprises polyethylene homopolymer or copolymer.

A preferred multilayer composite structure 20 for use as a bodyboard is illustrated in FIG. 2. The composite structure includes a first foam layer 22 comprising polyethylene homopolymer or copolymer, a second foam layer 24 comprising polypropylene homopolymer or copolymer, and a coating 26 disposed between and bonding the first and second foam layers together at a bond strength of at least about 4 lb_f/inch. The composition of coating 26 is as described above with respect to coating 14. For bodyboard applications, first foam layer 22 preferably comprises low density polyethylene having a density ranging from about 0.4 to about 15 pounds/ft³ and a thickness ranging from about 1/16 to about 1 inch, while second foam layer 24 preferably comprises polypropylene homopolymer having a density ranging from about 0.5 to about 10 pounds/ft³ and a thickness ranging from about 1 to about 4 inches.

Coating 26 is preferably as thin as possible, ranging from about 1 to about 5 mils.

The composite structure 20 is highly advantageous when used to form a bodyboard, with the PE foam sheet 22 providing comfort, grippability, and durability and the PP foam sheet 24 providing stiffness for good maneuverability while surfing. In addition, the coating 26 in accordance with the present invention provides a strong bond between the PE and PP foam sheets. If desired, an additional PE foam sheet, similar or identical to first foam layer 22, can be bonded to surface 28 of PP foam sheet 24 via a second coating layer 26 disposed between the additional PE foam sheet and surface 28 of PP foam sheet 24. In this configuration, relatively thin PE foam sheets form "skin" layers around a relatively thick "core" PP foam layer. This is a particularly advantageous configuration for bodyboard use as the outermost principle surfaces of the composite have the comfort and grippability of PE foam with a rigid PP foam core for enhanced wave riding performance.

Having now described composite structures in accordance with the invention, a preferred method for making composite structure 10 (FIG. 1) will be discussed with reference to FIG. 3. Foam sheet 12 is unwound from a storage roll 30 and sent to nip roller 32. Simultaneously, coating 14 is extruded onto surface 16 of foam sheet 12 between nip roller 32 and chill roller 34. This is a result of placing resin pellets of the polymer(s) used to make coating 14 into hopper 36, from which they enter extruder 38 wherein the pellets are mixed and melted. The resulting molten polymer is extruded into and through die 40 and onto surface 16 of foam sheet 12 as shown. Chill roller 34 is maintained at a sufficiently low temperature, e.g., less than about 65 °F, to cause the extruded polymer blend to solidify into coating 14 in adherence with foam sheet 12. In addition, nip roller 32 and chill roller 34 are urged against one another,

e.g., by mechanical or pneumatic means, with sufficient pressure to facilitate the bonding of the coating to the foam by squeezing the film and foam together as they pass between the two rollers. A third roller 42 may also be included to keep the resultant composite structure 10 in contact with chill roller 34 for a full half revolution about the chill roller, and to again apply pressure to the film/foam composite to facilitate bonding of the two materials. The finished composite structure 10 is then wound on storage roll 44.

The foregoing process is known as an extrusion coating process because the film is extruded in a molten state onto a previously formed and solidified foam sheet, whereon the film congeals and solidifies. Such a process is well known and further described, e.g., in U.S. Pat. No. 3,616,020. It is to be understood, however, that a method in accordance with the present invention is not limited to the illustrated extrusion coating process. Many alternatives are possible. For instance, instead of the 'off-line' extrusion coating process illustrated in FIG. 3, wherein a previously made foam sheet is taken from a storage roll, an 'in-line' process may be employed wherein the foam sheet can be extruded from a die and allowed to travel a sufficient distance to solidify before being coated, without the intermediate steps of winding and unwinding the foam on and from a storage roll. As a further alternative, a coextrusion process may be used in which the coating and foam are simultaneously extruded from separate dies and brought into contact with one another while both are still in a molten state.

In order to make the composite structure 20 as shown in FIG. 2, either the PE foam sheet 22 or PP foam sheet 24 may be coated with coating 26, e.g., by extrusion coating as shown in FIG. 3. Thereafter, the other foam sheet is laminated to the coated surface, i.e., to coating 26, preferably by applying heat to one or both surfaces to be bonded, and then

pressing the coated foam and non-coated foam together, e.g., between a pair of nip rollers. Alternatively, the entire three-layer structure can be coextruded.

5 These and other aspects and advantages of the invention may be further understood by reference to the following examples, which are provided for illustrative purposes only and are not intended in any way to be limiting.

10

EXAMPLES

LDPE foam sheet having a density of 8 pounds/ft³ (pcf) and a thickness of 3/16 inch was made using a standard extrusion process as described above. The sheet was wound in the form of a roll. The roll was mounted on an extrusion coating apparatus for applying a coating in accordance with the present invention on one surface of the foam sheet.

In the extrusion coating apparatus, resins used for the various coating formulations of Examples 1-8 were melted in a single screw extruder, sent through a cast die, and coated onto one surface of the LDPE foam sheet. The coated foam sheet then traveled between a pair of nip rollers. The resultant coatings for Examples 1-6 had a thickness of approximately 5 mils (0.005 inch) while the coatings for Examples 7-8 had a thickness of approximately 3.5 mils.

The resins used for each of the coatings in Examples 1-8 (the control sample had no coating) are summarized in Table 1.

25

TABLE 1

Resin	D e s c r i p t i o n
EPR	ADFLEX KS359P ethylene/propylene rubber having between 50 and 75 wt.% ethylene and dispersed in polypropylene; commercially available from Montell North America, Inc., Wilmington, Delaware.
LDPE	DOW LDPE 4012 low density polyethylene, commercially available from Dow Chemical, Midland, MI, having a density of 0.916 g/cc and a MI of 12.
MC-EAO1	ATTANE 4404 metallocene-catalyzed (homogeneous) ethylene/alpha-olefin (octene) copolymer having a density of 0.904 g/cc and a MI of 4.0; commercially available from Dow Chemical.
EAA	PRIMACORE 3440 ethylene/acrylic acid copolymer having a density of 0.938 g/cc and a MI of 10.5; commercially available from Dow Chemical.
MC-EAO2	AFFINITY PT1450 metallocene-catalyzed (homogeneous) ethylene/alpha-olefin (octene) copolymer having a density of 0.902 g/cc and a MI of 7.5; commercially available from Dow Chemical.
EVA	ESCORENE LD723.28 ethylene/vinyl acetate copolymer having a vinyl acetate content of 19.3 wt.%, a density of 0.94 g/cc, and a MI of 22.5; commercially available from ExxonMobil Chemical.

The following summarizes the extrusion-coating conditions for Examples 1-6:

5

Screw speed: 33-34 rpm

Total output rate: 88-91 Kg/hr

Melt temperature (measured at the die): 370-373 °F

Die pressure: 1200-2000 psi

Nip roll temperature: 65 °F

10

For Examples 7-8, the extrusion-coating conditions were as follows:

Screw speed: 18 rpm

Total output rate: 95.5 Kg/hr

Melt temperature (measured at the die): 347 °F

15

Die pressure: 500 psi

Nip roll temperature: 65 °F

Samples of the coated and uncoated ("control") foam sheets were bonded to the surface of a polypropylene plank having a thickness of about 2.25 inches and a density of either 1.5 pcf or 1.9 pcf (Example 7 only) using a hot air lamination process in which both surfaces to be bonded together were contacted with air maintained at 400 °F, and then the two foams were pressed together by squeezing them between a pair of nip rollers such that the two heated surfaces were urged together to form a bond. In the case of the coated samples (Examples 1-8), the coated surface of the LDPE foam sheet was heated and brought into contact with the heated surface of the PP foam.

The bond strengths between the LDPE and PP foams of the resultant composite structures were then tested using an INSTRON measurement device in accordance with ASTM F904-98 as follows:

1. Test samples of each foam sheet were prepared, each sample being 1 inch wide and 3 inches in length;
2. Initiated separation of the foam sheets at the foam/foam interface of each test sample at one end thereof;
3. Clamped each separated end of the test specimen in one of the two jaws of the INSTRON device using a starting jaw distance of 25.4 mm (1.0 inch); and
4. Activated the INSTRON device by causing the jaws to separate from one another at a speed of 4 inches/minute (this was slower than 10 inches/minute as specified in the ASTM procedure, due to the fact that the bond strength of a foam/foam laminate was tested, as opposed to a film/film laminate, for which a higher separation speed is more appropriate). The maximum force required to separate each test specimen was measured and recorded. This value is reported as the "Bond Strength" in Tables 2-4 (i.e., maximum separation force/inch width of the tested specimen).

TABLE 2

	Control	Example 1	Example 2	Example 3	Example 4	Example 5	Example 6 (Compar.)
Coating	None	Ethylene-Propylene Rubber (EPR)	EPR/LDPE blend at 70%/30% by weight	MC-EAO1	Ethylene/Acrylic Acid Copolymer (EAA)	MC-EAO2	MC-EAO2/LDPE blend at 70%/30% by weight
Bond Strength, lbf/inch	1.51	6.3	4.74	5.46	5.03	5.04	3.47
% Increase in Adhesion Strength*	--	317%	214%	262%	233%	233%	130%
Comments	PE foam peels easily from PP foam.	Excellent adhesion between PE and PP surfaces.	Excellent adhesion between PE and PP surfaces.	Excellent adhesion between PE and PP surfaces.	Excellent adhesion between PE and PP surfaces.	Excellent adhesion between PE and PP surfaces.	Moderate adhesion between PE and PP surfaces.

* ((Force required for coated sample-Force required for uncoated sample)/(Force required for uncoated sample)) x 100

As indicated by the results in Table 2, all coatings in Examples 1-6 provided an increase in adhesion between the LDPE and PP foam sheets vs. the Control structure, which had no coating disposed between the foam sheets. The composite structures of Examples 1-5 demonstrated a sufficiently high bond strength for commercial use. In fact, the bond strength between the foam sheets of Examples 1-5 was so strong that, instead of delamination between the foam sheets, most of the separation occurred within the LDPE foam sheet as cohesive failure. The bond strength of the Example 6 composite structure was observed to be insufficient for commercial applications. The minimum bond strength for commercial applicability thus appears to be about 4 lbf/inch.

For Example 7, an EVA-coated LDPE foam sheet was laminated to a "beaded" PP foam plank having a density of 1.9 pcf. The beaded PP foam was made by using moldable polypropylene beads, which were impregnated with a blowing agent (n-butane) and then flash expanded to

make cellular beads. The cellular beads were then molded to give a shape of a plank. Bond-strength data is set forth in Table 3.

TABLE 3

	Control	Example 7
Coating	None	3.5 mil EVA
Bond Strength, lb _f /inch	1.51	13.96
% increase in adhesion	--	825%*
Comments	PE foam peels easily from PP foam	Excellent adhesion between PE and PP foam surfaces.

* (Force required for coated sample-Force required for uncoated sample)/(Force required for uncoated sample) x 100

Example 8 was similar to Example 7, except that the EVA-coated LDPE foam sheet was laminated to an extruded PP foam plank having a density of 1.5 pcf. Bond-strength data is set forth in Table 4.

TABLE 4

	Control	Example 8
Coating	None	3.5 mil EVA
Bond Strength, lb _f /inch	1.51	15.83
% increase in adhesion	--	948.3%
Comments	PE foam peels easily from PP foam	Excellent adhesion between PE and PP foam surfaces.

* (Force required for coated sample-Force required for uncoated sample)/(Force required for uncoated sample) x 100

As indicated by the results in Tables 3-4, EVA coatings provide an exceptional degree of adhesion between LDPE and PP foam sheets.

While the invention has been described with reference to illustrative examples, those skilled in the art will understand that various

modifications may be made to the invention as described without departing from the scope of the claims which follow.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
22